



ULTRA-CLEAR DECAL WINDOW FILM

OPTICAL Clarity

OPTI-CLEAR CLARITY FOR SECOND-SURFACE (INSIDE LOOKING OUT) APPLICATIONS.

Premium 4 mil optically clear PVC film with a super-smooth PET liner, engineered for high-end window displays and glass applications. It features a 25um solvent acrylic adhesive providing clean, 6-month removability and supports second-surface printing with a white ink option for impactful second-surface displays. Available in 54" and 60" x 150 ft. rolls

Print compatibility: Eco-Solvent, UV, and Latex inks.

KEY HIGHLIGHTS

- 4 mil premium high-gloss printable clear PVC film
- 54", 60"
- Removable up to 6 months

DAF Products Inc.
Graphic Media Specialists



DIGITAL SELECTOR GUIDE



WEBSITE



DATA SHEET

DAF Products Inc.

DAF Ultra Clear Decal Window Film

TECHNICAL SPECIFICATIONS

PARAMETER	TYPE	VALUE
Film	TYPE	100um Optical clear PVC films
Film	Transparency	97%
Film	Finish	GLOSS (95@60°)
Film	E value (% at break)	220% / 230% (MD/CD)
Film	Shrinkage	3% / 0.5% (MD/CD)
Adhesive	Materials	25um solvent based acrylic glue
Adhesive	Type	Clear soft removable
Adhesive	Init tack (20min peel)/(N/in)	4 N
Adhesive	Hold: 9.8 N/in ² (Hours)	72 Hours
Adhesive	180° Peel (N/in)	5 N
Liner	Thickness	125um
Liner	Type	Clear matte PET
Shelf time	—	24 Months
Applying temp	—	-5°C - 50°C
Outdoor durability	—	24 Months

PRINTING INK COMPATIBILITY

Solvent	Eco-Sol	Aqueous Dye	Aqueous Pigment	UV	Latex
Y	Y	—	—	Y	Y

APPLICATION COMPATIBILITY

Billboard	Rigid Board	Window Graphic	Wall	Floor	Vehicle	Signs
—	—	Y	—	—	—	Y